Digital Pressure Controller XY-PC800Z

Typical Feature

- Stainless steel 304 shell, Panel Mount dial diameter Φ80mm
- ☐ 4-Digits LED Display,
- ☐ Multi-unit convert MPa/Kgf/cm²/PSI
- ☐ Accuracy level:0.5%FS
- ☐ Power supply 12 or 24VDC; Optional 220VAC
- ☐ Relay output signal NONC
- ☐ High precision, quick response time, stable and easy setting up







Brief Introduction

XY-PC800Z is a Panel Mount Intelligent Digital Pressure Controller, with 80mm diameter stainless steel shell, integrating pressure measurement, display and control function. It has a variety of excellent functions, such as one-button reset, Multi-pressure Unit Converting and it's easy to reset setting, adjusting and installation.

This series of digital pressure controller has one relay, which can be set up normally open and normally close; these alarm points to control high and low pressure of air or liquid, in addition, it is with one key reset, at the same time, calibration, shifting display unit, setting return difference and others option functions.

The intelligent pressure controller is equipped with high-precision instrument amplifier to amplify pressure signal, built-in temperature compensation sensor, is the high precision equipment for detecting and monitoring pressure, strong anti-electromagnetic interference (EMI), surge protection, reverse protection and so on

XY-PC800Z Intelligent Digital Pressure Controller can be widely used in Automatic System, Mobile Working Machines, Medical Equipment, Pump, Compressor, Energy and Water Treatment, Agricultural Equipment, Test System, Hydraulic System and Pneumatic System.

Suggested Applications


- Equipment Automation
- Mobile Work Machine
- Water Pump and Air compressor
- 🖶 🛮 Electromechanical Equipment Automation
- 🖶 🛮 Energy and Water Treatment System
- 🖊 Medical Equipment
- Hydraulic and Pneumatic Systems
- 🖶 🛮 Agricultural Equipment
- 📥 Test Jig
- Customized Applications

More details for XY-PC800Z, please contact us.


Specification

Model	XY-PC800Z					
Gauge Pressure Range	0···0.2···0.6···1.0···1.6···2.5···5···10···25···40···60···100···160MPa					
Micro Pressure Range	0~5···10···25···50···100KPa					
Vacuum Pressure Range	-100~0KPa					
Overload Capacity	200% (≤10MPa); 150%(>10MPa)					
Measurement Medium	Gas or oil or other Liquid with Compatibility of SS 304 or 316					
Accuracy Level	0.5%FS;					
Long-Term Stability/Year	Typical: ±0.5% FS;					
Sampling frequency	5times/second					
Alarm Point	Any pressure @whole measurement range					
Output	Relay Signal					
Relay Capacity	220VAC 5A; 24VDC 5A					
Electric protection	Short-circuit protection; Reverse connect protection; Anti-EMI					
Display	4 digits LED					
Operating temperature	-20~80°C					
Compensation	-10~60°C					
Power Supply	12/24VDC					
Mechanical Connector	M2081.5; G1/2; G1/4					


Dimension(mm)



Output



Outlet Line



*Reverse control is available
(Low pressure to start, high pressure to stop)

How To Order

XY-	PG	- 280	- E	P	- 60 H -	- 1	- P2	- J	- M3	- B1	- T1	- L
	Category	Туре	Setup	Pressure Connection	Pressure Range	Accuracy	Power	Output	Thread	Electrical Connection	ledium Temperature	Additional
į		200 High Accuracy	E Lower Mount	Mone General Thread	XK (0-XKPa)	1 0.40%	PO Battery	R R5485	M1 M20*1.5	B Cable Outlet	T1 -5~40°C	LC LCD Display
		210 High Accuracy Pressure&Temperture	Z Panel Mount	P Diaphrago Seals	XB (0-XBar)	2 0.20%	P2 24V	A 4-20mA	M2 G1/4	C Circular Connector	T2 -20`80°C	LE LED Display
		270 Explosion-Proof	6 Wireless	DP Differential Pressure	XM (0-XMPa)	3 0.10%	P4 220V	Jl Relay	M3 G1/2	CC Customized	T9 Customized	I Explosion-Proof
		280 BOmm Dial Size LCD Display	F Peak Record	KF Clamp	OC Dustomized	4 0.50%	P5 380V	J2 Dual Relay	M4 L/2NPT			
		260 60mm Dial Size	V Vacuum Switch	DN Flange		5 0.25%	P6 12V	CC Customized				
	PG Pressure Gauge	300 100mm Dial Size	W Water Pump Switch	9999 Customized		9 Customized	P9 Customized		M7 ZG1/4			
		380 80mm Dial Size LED Display							M9 Customized			
		560 Digital Remote-transimission										
		625 Contact 60mm Dial Size										
		825 Contact 80mm Dial Size										
		925 Contact 90mm Dial Size										
f		628 60mm Dial Size]									
		828 80mm Dial Size										
	PS Pressure Switch	928 100mm Dial Size										
	13 Headure Salicit	650 Switch Box with Plactic Shell										
		600 Switch Box with Full Metal Shell										
		700 Mechanical										
F		600 60mm Dial Size]									
	PC Pressure Control	800 80mm Dial Size										
		900 100mm Dial Size										

Remark: 1. This form is for whole Pressure Measurement and Pressure Control products, please read Product Date Sheet to get referance informations
2. If you may not find right information in this form, Please contact us to get future details

Shanghai XuYan Precision Technology Co., Ltd.

Address: No. 969, YunHan Road Pudong District Shanghai City China

Tel: +86 21 59241315

Email: sales@xvyanprecision.com **Website**: www.xvyanprecision.com

Product Manager: Tyler Tou **Cell:** +86 189 1797 0680

Email: ttao@Xuyanpercision.com