Digital Pressure Switch XY-PS650

Typical Feature

- ☐ 4-Digits LED Display,
- ☐ Multi-unit convert MPa/Kgf/cm²/PSI
- ☐ Accuracy level:0.5%FS
- ☐ Power supply 24VDC; Optional 220VAC
- ☐ Dual relay, output signal NONC
- ☐ High precision, quick response time, stable and easy setting up



Brief Introduction

XY-PS650 is an Intelligent Digital Pressure Switch Box, Plastic shell, integrating pressure measurement, display and control function. It has a variety of excellent functions, such as one-button reset, Multi-pressure Unit Converting and it's easy to reset setting, adjusting and installation.

Two relays are built in, this series of digital pressure switches have dual relays, which can be set up two ways of normally open and normally close alarm points separately, also are able to control two ways of high and low pressure of air or liquid, in addition, it is with one key reset, at the same time, calibration, shifting display unit, setting return difference and others option functions.

The intelligent pressure switch is equipped with high-precision instrument amplifier to amplify pressure signal, built-in temperature compensation sensor, is the high precision equipment for detecting and monitoring pressure, strong anti-electromagnetic interference (EMI), surge protection, reverse protection and so on

XY-PS650 Intelligent Digital Pressure Switch Box can be widely used in Automatic System, Mobile Working Machines, Medical Equipment, Pump, Compressor, Energy and Water Treatment, Agricultural Equipment, Test System, Hydraulic System and Pneumatic System.

Suggested Applications


- Equipment Automation
- Mobile Work Machine
- Water Pump and Air compressor
- 🖶 🛮 Electromechanical Equipment Automation
- 🖶 Energy and Water Treatment System
- 🖶 Medical Equipment
- Hydraulic and Pneumatic Systems
- 📥 🛮 Agricultural Equipment
- 🖶 Test Jig
- Customized Applications


More details for XY-PS650, please contact us.

Specification


Model	XY-PG650						
Cauga Pragaura Panga	-100KPa~0···10···50···100KPa						
Gauge Pressure Range	0~1Bar···2···6···10···16···25···50···100···250···400···600Bar						
Overload Capacity	200%(≤100Bar); 150%(>100Bar)						
Measurement Medium	Gas or oil or other Liquid with Compatibility of SS 304 or 316						
Accuracy Level	0.5%FS; 0.25%FS;						
Long-Term Stability/Year	Typical:±0.5% FS;						
Alarm Point	Any pressure @whole measurement range						
Output	Relay; NONC						
Load Capacity	220VAC 5A;24VDC 5A						
Display	4 digits LED						
Operating temperature	-40~85°C						
Compensation	-20~60°C						
Power Supply	24VDC ;220VAC; 380VAC are optional						
Electrical Protection	Anti-EMI; Reverse connection protection (Current Power Supply)						
Sampling Frequency	5 times/Second						
Standard Mechanical Joint	anical Joint M20*1.5; NPT1/4, G1/4, Customized types						
Electronic Connection	Circular Connector						

Dimension(mm)






Connecting Description:



Mounting Bracket Size:



How To Order

XY-	PG	- 280	- E	P	- 60 M -	- 1	- P2	- J	- M3	- B1	– T1	– L
	Category	Туре	Setup	Pressure Connection	Pressure Range	Accuracy	Power	Output	Thread	Electrical Connection	ledium Temperature	Additional
PG	Pressure Gauge	200 High Accuracy	E Lower Mount	Mone General Thread	XK (O-XKPa)	1 0.40%	PO Battery	R R5485	M1 M20*1.5	B Cable Outlet	T1 -5~40°C	LC LCD Display
		210 High Accuracy Pressure&Temperture	Z Panel Mount	P Disphrage Seals	XB (0-XBar)	2 0.20%	P2 24V	A 4-20mA	M2 G1/4	€ Circular Connector	T2 -20`80°C	LE LED Display
		270 Explosion-Proof	G Wireless	DP Differential Pressure	XM (0-XMPa)	3 0.10%	P4 220V	Jl Relay	M3 G1/2	CC Customized	T9 Customized	I Emplosion-Proof
		280 BOmm Dial Size LCD Display	F Peak Record	KF Clamp	OC Dustomized	4 0.50%	P5 380V	J2 Dual Relay				
		260 60mm Dial Size	V Vacuum Switch	DN Flange		5 0.25%	P6 12Y	CC Customized				
		300 100mm Dial Size	Water Pump Switch	9999 Customized		9 Customized	P9 Customized		M7 ZG1/4			
		380 80mm Dial Size LED Display							M9 Customized			
		560 Digital Remote-transimission										
		625 Contact 60mm Dial Size										
		825 Contact 80mm Dial Size										
L		925 Contact 90mm Dial Size										
PS	Pressure Switch	628 60mm Dial Size										
		828 80mm Dial Size										
		928 100mm Dial Size										
		650 Switch Box with Plactic Shell										
		600 Switch Box with Full Metal Shell										
		700 Mechanical										
PC	Pressure Control	600 60mm Dial Size										
		800 80mm Dial Size										
		900 100mm Dial Size										

Remark: 1. This form is for whole Pressure Measurement and Pressure Control products, please read Product Date Sheet to get referance informations
2. If you may not find right information in this form, Please contact us to get future details

Shanghai XuYan Precision Technology Co., Ltd.

Address: No. 969, YunHan Road Pudong District Shanghai City China

Tel: +86 21 59241315

Email: sales@xvyanprecision.com **Website**: www.xvyanprecision.com

Product Manager: Tyler Tou **Cell:** +86 189 1797 0680

Email: ttao@Xuyanpercision.com