# **Digital Vacuum Pressure Controller XY-PC800V**

## Typical Feature

Plastic shell, dial diameter Ф80п	]	Plastic shel	I. dial	diameter	Ф80m
-----------------------------------	---	--------------	---------	----------	------

☐ 4-Digits LED Display,

☐ Multi-unit convert MPa/Kgf/cm²/PSI

☐ Measurement range -120KPa~0

☐ Accuracy level:0.5%FS

☐ Power supply 12 or 24VDC; Optional 220VAC

☐ Relay output signal NONC

☐ High precision, quick response time, stable and easy setting up



#### **Brief Introduction**

XY-PC800V is an Intelligent Vacuum Digital Pressure Controller, with 80mm diameter Plastic shell, integrating Vacuum pressure measurement, display and control function. It has a variety of excellent functions, such as one-button reset, Multi-pressure Unit Converting and it's easy to reset setting, adjusting and installation.

This series of digital pressure controller has one relay, which can be set up normally open and normally close; these alarm points to control high and low pressure of air or liquid, in addition, it is with one key reset, at the same time, calibration, shifting display unit, setting return difference and others option functions.

The intelligent pressure controller is equipped with high-precision instrument amplifier to amplify pressure signal, built-in temperature compensation sensor, is the high precision equipment for detecting and monitoring pressure, strong anti-electromagnetic interference (EMI), surge protection, reverse protection and so on

XY-PC800V Intelligent Digital Pressure Controller can be widely used in Vacuum Pump, Vacuum Equipment, Vacuum Control System, Alternative Vacuum Pressure Meter Switch,

Mechanical Vacuum Switch

## Suggested Applications

Vacuum Pump

🖶 Vacuum Equipment

Vacuum Control System

Alternative Vacuum Pressure Meter Switch

Alternative Mechanical Vacuum Switch


Customized Applications


More details for XY-PC800V, please contact us.

## Specification


Model	XY-PC800V				
Vacuum Pressure Range	-120~0KPa				
Overload Capacity	200%				
Measurement Medium	Gas or oil or other Liquid with Compatibility of SS 304 or 316				
Accuracy Level of Display	0.1KPa				
Accuracy Level of Control	1KPa				
Alarm Point	Any pressure @whole measurement range				
Output	Relay Signal				
Relay Capacity	220VAC 5A; 24VDC 5A				
Electric protection	Short-circuit protection; Reverse connect protection; Anti-EMI				
Display	4 digits LED				
Operating temperature	-20~80°C				
Compensation	-10~60°C				
Power Supply	12/24VDC				
Mechanical Connector	M2081.5; G1/2; G1/4				

## Dimension(mm)






## Output



## **Outlet Line**



\*Reverse control is available (Low pressure to start, high pressure to stop)

#### How To Order

XY-	PG	- 280	- E	P	- 60 <b>H</b> -	- 1	- P2	- J	- <b>M</b> 3	– В1	- T1	- L
	Category	Туре	Setup	Pressure Connection	Pressure Range	Accuracy	Power	Output	Thread	Electrical Connection	ledium Temperature	Additional
	PG Pressure Gauge	200 Nigh Accuracy 210 Nigh Accuracy Fressure&Temperture 210 Nigh Accuracy Fressure&Temperture 220 Emplois entropfroof 220 DNm Dial Size LOD Display 200 ONmo Dial Size 300 ONmo Dial Size 300 DNm Dial Size 300 DNm Dial Size 500 Digital Remotertransimission 550 Digital Remotertransimission 550 Contact Onm Dial Size	E Lower Mount Z Panel Mount G Wireless F Peak Record Y Vecuum Switch W Water Pump Switch	Mone   General Thread   P   Diaphrago Seals   DP   Differential Pressure   KF   Claup   DN   Flange   9999   Customized	XK (O-XKPa) XB (O-XBar) XM (O-XMPa) CC Distonized	1 0.40% 2 0.20% 3 0.10% 4 0.50% 5 0.25% 9 Oustomized	PO Battery P2 24Y P4 220V P5 380V P6 12Y P9 Customized	R R5485 A 4-20mA J1 Relay J2 Dual Relay CC Customized		B Cable Dutlet C Circular Connector CC Customized	T1 -5~40°C T2 -20~80°C T9 Customized	LC LCO Display LE LED Display I Explosion-Proof
	PS Pressure Switch PC Pressure Control	SIGN Contact NOWN Disk Size SIGN Contact NOWN Disk Size SIGN Contact NOWN Disk Size SIGN NOWN Disk Size										

Remark: 1. This form is for whole Pressure Measurement and Pressure Control products, please read Product Date Sheet to get referance informations
2. If you may not find right information in this form, Please contact us to get future details

## Shanghai XuYan Precision Technology Co., Ltd.

Address: No. 969, YunHan Road Pudong District Shanghai City China

**Tel:** +86 21 59241315

Email: sales@xvyanprecision.com Website: www.xvyanprecision.com

Product Manager: Tyler Tou Cell: +86 189 1797 0680

Email: ttao@Xuyanpercision.com

All sales subject to standard terms and conditions

All specifications are subject to change without notice